



Canon RF 24-105mm F2.8 L IS USM Z MILC Obiettivo zoom Nero

Marchio : Canon
Codice prodotto: 6347C005
Nome del prodotto : RF 24-105mm F2.8 L IS USM Z

- Giornalismo/reportage, filmmaking, documentari, contenuti aziendali, matrimoni/eventi
- Livello professionale
- Obiettivo performante in condizioni di luce scarsa, video ibridi, serie L
RF 24-105mm F2.8 L IS USM Z
Canon RF 24-105mm F2.8 L IS USM Z. Componente per: MILC, Struttura lente: 23/18, Tipo di lente:
Obiettivo zoom. Marche compatibili: Canon, Attuatore AF: USM, Colore dell'obiettivo: Nero. Colore del
prodotto: Nero, Tipo di montaggio: Bayonet. Paese di origine: Giappone, Numero di livelli per pallet: 3 pz,
Numero di scatole per strato: 24 pz. Diametro: 8,85 cm, Dimensione filtro: 82 mm, Lunghezza: 199 mm



Lens system		Performance	
Component for *	MILC	Camera brands compatibility *	Canon
Lens type *	Zoom lens	Circular aperture	✓
Lens structure (elements/groups) *	23/18	Lens coating features	Super Spectra Coating (SSC)
Lens viewing angle, horizontal	74° - 19° 20'	Number of Ultra-low Dispersion (UD) elements	4
Focus adjustment	Auto/Manual	Lens hood	✓
Lens viewing angle, vertical	53° - 13°	Lens hood model	EW-88E
Lens viewing angle, diagonal	84° - 23°20'	Design	
Focal length range	24 - 105 mm	Product colour	Black
Minimum aperture number *	22	Mounting type	Bayonet
Number of diaphragm blades	11	Dustproof	✓
Closest focusing distance *	0.45 m	Weatherproof	✓
Maximum aperture number *	2.8	Logistics data	
Macro ratio	1:3.4	Country of origin	Japan
Number of aspheric elements	3	Layers per pallet	3 pc(s)
Image sensor format	Full frame	Master (outer) cases per pallet layer	24 pc(s)
Lens mount interface *	Canon RF	Weight & dimensions	
Teleconverter/Extender compatible	✗	Length	199 mm
Control ring	✓	Weight	1.33 kg
Image stabilizer	✓	Diameter *	8.85 cm
Image stabilizer type	Optical Image Stabilization (OIS)	Filter size *	82 mm
Image stabilizer number of stops	5.5	Packaging data	
Image stabilizer number of stops (OIS)	5.5	Package width	184 mm
Image stabilizer number of stops (IBIS x OIS)	8	Package depth	184 mm
Performance		Package height	312 mm
Auto focus	✓	Package weight	2.11 kg
Manual focus	✓	Package type	Box
AF actuator	USM	Packaging content	
Lens colour	Black	Lens cap included	✓
		Lens cap model	E-82 II
		Rear lens cap included	✓

Packaging content

Rear lens cap model	RF
User guide	✓



4549292223156

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 16-APR-2025. Prints or copies of Information are only valid on the printed Publication date