



Canon EOS R50 MILC 24,2 MP CMOS 6000 x 4000 Pixel Nero

Marchio : Canon **Famiglia del prodotto:** EOS **Codice prodotto:** 5811C003
Nome del prodotto : EOS R50

EOS R50, Nero
Canon EOS R50. Tipologia fotocamera: MILC, Megapixel: 24,2 MP, Tipo sensore: CMOS, Risoluzione massima immagine: 6000 x 4000 Pixel. Sensibilità ISO (max): 32000. Velocità massima dell'otturatore della fotocamera: 1/8000 s. Wi-Fi. Tipologia HD: 4K Ultra HD, Risoluzione massima video: 3840 x 2160 Pixel. Touch screen. Tipo di mirino: Elettronico. Peso: 328 g. Colore del prodotto: Nero



| Picture quality | | Viewfinder | |
|----------------------------------|--|-------------------------------------|--|
| Image sensor aspect ratio | 3:2 | Viewfinder frame rate (smooth mode) | 120 fps |
| Camera type * | MILC | Viewfinder resolution (approx.) | 2360000 pixels |
| Megapixel (approx.) * | 24.2 MP | Ports & interfaces | |
| Sensor type * | CMOS | USB version * | 2.0 |
| Maximum image resolution * | 6000 x 4000 pixels | USB connector | USB Type-C |
| Still image resolution(s) * | 6000 x 4000, 3984 x 2656, 2976 x 1984, 2400 x 1600, 5328 x 4000, 3552 x 2664, 2656 x 1992, 2112 x 1600, 4000 x 4000, 2656 x 2656, 1984 x 1984, 1600 x 1600 | HDMI * | ✓ |
| Image stabilizer * | ✗ | HDMI version | 2.0 |
| Supported aspect ratios | 1:1, 3:2, 4:3, 16:9 | HDMI connector type | Micro |
| Image sensor size (W x H) | 22.3 x 14.9 mm | Microphone in | ✓ |
| Sensor format | Advanced Photo System type-C (APS-C) | Network | |
| Built-in low-pass filter | ✓ | Bluetooth * | ✓ |
| Image formats supported * | JPEG, RAW, C-Raw, HEIF | Bluetooth version | 4.2 |
| Focusing | | Bluetooth Low Energy (BLE) | ✓ |
| Focus * | TTL | Wi-Fi * | ✓ |
| Focus adjustment * | Auto/Manual | Wi-Fi standards | 802.11b, 802.11g, Wi-Fi 4 (802.11n) |
| Auto focusing (AF) modes * | Continuous Auto Focus, One Shot Focus, Servo Auto Focus | Camera | |
| Auto Focus (AF) object detection | Animal, Bird, CAT, Dog, People, Vehicle | White balance * | Auto, Cloudy, Custom modes, Daylight, Flash, Fluorescent, Manual, Shade, Tungsten |
| Face tracking | ✓ | Scene modes * | Children, Close-up (macro), Food, Group photo, HDR backlight control, Handheld night scene, Landscape, Panning, Panorama, Portrait, Self-portrait, Silent shutter, Smooth skin, Sports |
| Auto Focus (AF) lock | ✓ | | Aperture priority, Auto, Intelligent auto, Manual, Program, Scene, Shutter priority |
| Auto Focus (AF) assist beam | ✓ | | |
| Exposure | | Shooting modes * | |
| ISO sensitivity (min) * | 100 | Self-timer delay * | 2,10 s |
| ISO sensitivity (max) * | 32000 | Dioptr correction | ✓ |
| ISO sensitivity | 100, 6400, 25600, 51200 | Dioptr adjustment (D-D) | -3 - 1 |
| Light exposure modes * | Aperture priority AE, Auto, Manual, Shutter priority AE | Histogram | ✓ |
| Light exposure control | Program AE | Live view | ✓ |
| Light exposure correction * | ± 3EV (1/3EV step) | Direct printing | ✓ |

| Exposure | | Camera | |
|---|--|--|-----------------------------------|
| Light metering * | Centre-weighted, Evaluative (Multi-pattern), Partial, Spot | GPS (satellite) | ✗ |
| Auto Exposure (AE) lock | ✓ | Orientation sensor | ✓ |
| Number of measurement zones | 384 | Anti-dust function | ✗ |
| Exposure bracketing (AEB) | ± 3EV (1/2EV; 1/3EV stop) | Smartphone/tablet remote support | ✓ |
| Anti-flicker shooting | ✓ | View on smartphone | ✓ |
| Shutter | | Playback zoom (min) | 1.5x |
| Fastest camera shutter speed * | 1/8000 s | Playback zoom number of steps | 15 |
| Slowest camera shutter speed * | 30 s | Erase protection options | Folder, Memory card, Single image |
| Camera shutter type | Electronic | Tripod mounting supported * | ✓ |
| Flash | | Slideshow | ✓ |
| Flash exposure lock | ✓ | Image processor | DIGIC X |
| Flash guide number | 6 m | Design | |
| External flash connector | ✓ | Product colour * | Black |
| Flash exposure compensation | ✓ | Dustproof | ✗ |
| Flash exposure correction | ±3EV (1/3 EV step) | Splash proof | ✗ |
| Shoe mounting point | ✓ | Battery | |
| Shoe mounting point type | Hot shoe | Battery technology * | Lithium-Ion (Li-Ion) |
| Video | | Battery type | LP-E17 |
| Video recording * | ✓ | Number of batteries supported | 1 |
| Maximum video resolution * | 3840 x 2160 pixels | Battery level indicator | ✓ |
| HD type * | 4K Ultra HD | Battery level indicator number of levels | 4 |
| Video resolutions | 1920 x 1080, 3840 x 2160 pixels | Power | |
| Video formats supported | H.264, H.265 | USB Type-C charging port * | ✓ |
| Colour sampling | YCbCr4:2:0 8-bit, YCbCr4:2:2 10-bit | USB Type-C required charging power (min) * | 7.5 W |
| Audio | | USB Type-C required charging power (max) * | 7.5 W |
| Built-in microphone * | ✓ | Operational conditions | |
| Built-in speaker(s) | ✓ | Operating temperature (T-T) | 0 - 40 °C |
| Audio system | stereo | Weight & dimensions | |
| Wind filter | ✓ | Width | 116.3 mm |
| Audio formats supported | LPCM, AAC | Depth | 68.8 mm |
| Memory | | Height | 85.5 mm |
| Compatible memory cards * | SD, SDHC, SDXC | Weight | 328 g |
| Memory slots | 1 | Weight (including battery) | 375 g |
| Display | | Packaging data | |
| Display * | LCD | Quantity per pack | 1 pc(s) |
| Touchscreen * | ✓ | Package width | 172 mm |
| Display diagonal (metric) | 7.5 cm | Package depth | 196 mm |
| Display resolution | 1620000 dot | Package height | 141 mm |
| Display aspect ratio | 3:2 | Package weight | 921 g |
| Vari-angle LCD display | ✓ | Packaging content | |
| Viewfinder | | Neck strap included | ✓ |
| Viewfinder type | Electronic | AC adapter included * | ✗ |
| Magnification | 0.95x | Battery charger included | ✓ |
| Viewfinder screen size | 0.39" | Batteries included | ✓ |
| Viewfinder frame rate (power saving mode) | 60 fps | Logistics data | |
| | | Products per pallet | 120 pc(s) |



4549292205015

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 05-MAY-2025. Prints or copies of Information are only valid on the printed Publication date